

WEATHERLUX WALL EXIT LIGHT GEN2



PRODUCT DETAILS

Viewing distance: 16m
 Rated life: L70 B50 54000hrs
 Driver: Integral, Non-Dim
 Rating: IP65, IK08, Class II
 Operating temperature: 0°C to +40°C
 Housing: Polycarbonate (PC)
 Finishing: White
 Accessory: Complete with all pictograms
 Emergency: Maintained, DALI emergency (self-test if not connected to DALI), Replaceable lithium iron phosphate (LiFePO4) battery, 18 months shelf life
 Compliant: AS/NZS 2293
 Warranty: 5 years on fixture and lamp, 4 years on battery



APPLICATIONS

Surface mounted (wall), Internal/External
 Damp environments, Warehouses, Production facilities, Car parks, Schools, Coastal areas



| CODE | DESCRIPTION | POWER [~] | LUMENS [*] | EFFICACY | WEIGHT |
|---------|--|--------------------|---------------------|----------|--------|
| WLUX-WM | WEATHERLUX IP65 EXIT LIGHT GEN2 16M 5W MAINTAINED DALI EMERGENCY WHITE | 5W | | | 1.2KG |
| | EMERGENCY MODE | 2W | 71LM | 36LM/W | |

[~]Tested system powers from luminaire. ^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses. [^]Figures are interpolated / extrapolated from data at other versions.